



**VARATHANE®
PREMIUM FILL STICKS**

DESCRIPTION AND USES

Varathane® Premium Fill Sticks are a quick and easy way to repair scratches, nicks, dents or other minor imperfections in any wood surface. Premium Fill Sticks are suitable for touching up furniture, cabinets, trim, doors and floors. Premium Fill Sticks can be used to complement Varathane Premium Wood Stains or blend different Fill sticks to create custom colors.

PRODUCTS

SKU	DESCRIPTION (Fill Stick)
215362	Color Group 1
215363	Color Group 2
215364	Color Group 3
215365	Color Group 4
215366	Color Group 5
215367	Color Group 6
215368	Color Group 7
215369	Color Group 8
215370	Color Group 9
215371	Color Group 10
359932	Color Group 12

PRODUCT APPLICATION

SURFACE PREPARATION

If the area around the nick or dent is rough, sand the area smooth by sanding with #120 grit sandpaper in the direction of the grain. Remove all sanding dust with a vacuum or clean rag dampened with mineral spirits.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Prior to repairs, determine the Fill Stick color that best matches the wood project. See the front panel of the package for Fill Stick color identification. Test the Fill Stick in an inconspicuous area to ensure the chosen color will match the project. Work the Fill stick into the defect until filled. Remove excess material using a plastic putty knife.

DRY TIME

Dry time of product depends on depth of scratch or repair. Most repairs will dry within 5 minutes. If more than one filling is required, allow sufficient dry time between fillings.

PROTECTING YOUR PROJECT

If desired, additional protection of the repaired area can be achieved by applying a thin coat of Varathane Diamond Polyurethane. Apply the polyurethane with an artist acrylic paint brush and follow the manufacturer's directions for dry times.

	TECHNICAL DATA	VAR-25
	VARATHANE® PREMIUM FILL STICKS	

PHYSICAL PROPERTIES

		PREMIUM FILL STICKS
Resin Type		Waxes
Pigment Type		Inorganic and Organic
Solvents		None
Weight	Per Gallon	8.75 lbs.
	Per Liter	1.05 kg
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		None
Practical Coverage		Varies with wood type
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5 minutes
	Handle	5 minutes
	Full Cure	10 minutes
Shelf Life		3 years
Flash Point		NA
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
 11 Hawthorn Parkway
 Vernon Hills, Illinois 60061

Phone: 800-901-0411
www.rustoleum.com/varathane

Form: GDH-17
 Rev.: 030620